



Note - All dimensions are approximate and are subject to change without notice.

- * STANDARD FEATURES *
- Removes separable solids larger than 50 micron (325 mesh) and 20% heavier than liquid
 - Accommodates flow rates from 2,100 to 3,825 US GPM
 - 150 PSI working pressure
 - Carbon steel construction
 - Fully pressure tested

- * AVAILABLE OPTIONS *
- Inlet/Outlet Pressure Gauges
 - Clean Out Ports
 - Removable Dome for easy clean out
 - Automatic purge valve with timer
 - ASME certified for 150 PSIG @ 250°F
 - 304, 316 Stainless Steel construction

* PRESSURE DROP *

To determine pressure drop (PSI) at known flow rates, use the following formula:

$$P = \left(\frac{\text{GPM}}{1210} \right)^2$$

Weight (empty): 1221 lbs
 Weight (full): 2517 lbs
 Volume: 155.5 gallons

SBS SBS CORPORATION
 81 MILL STREET • ROCHESTER, MI 48307 • USA
 U.S. & Canada 1-800-662-8776 • Fax 1-248-652-4303 • www.sbcorporation.com

CUSTOMER:		
DRAWN BY: GSB	DATE: 3/6/01	SCALE: 1 : 20

CS-1200 Centrifugal Separator