



\* STANDARD FEATURES \*

- Removes separable solids larger than 50 micron (325 mesh) and 20% heavier than liquid
- Accommodates flow rates from 5,850 to 10,700 US GPM
- 150 PSI working pressure
- Carbon steel construction
- Fully pressure tested

\* AVAILABLE OPTIONS \*

- Inlet/Outlet Pressure Gauges
- Clean Out Ports
- Removable Dome for easy clean out
- Automatic purge valve with timer
- ASME certified for 125 PSIG @ 210°F
- 304 or 316 Stainless Steel construction

\* PRESSURE DROP \*

To determine pressure drop (PSI) at known flow rates, use the following formula:

$$P = \left( \frac{\text{GPM}}{3375} \right)^2$$

Weight (empty): 3190 lbs  
 Weight (full): 8530 lbs  
 Volume: 641 gallons

Note - All dimensions are approximate and are subject to change without notice.

**SBS** SBS CORPORATION  
 81 MILL STREET • ROCHESTER, MI 48307 • USA  
 U.S. & Canada 1-800-662-8776 • Fax 1-248-652-4303 • www.sbcorporation.com

CUSTOMER:		
DRAWN BY: GSB	DATE: 6/5/02	SCALE: NTS

CS-2000 Centrifugal Separator