

* STANDARD FEATURES *

- Removes separable solids larger than 50 micron (325 mesh) and 20% heavier than liquid
- Accommodates flow rates from 125 to 240 US GPM.
- 150 PSI working pressure
- Carbon steel construction
- Fully pressure tested


* AVAILABLE OPTIONS *

- 150# Flanged Inlet & Outlet
- 3" x 4" clean out port
- Bracket Mounting
- Foot Mounting
- Inlet/Outlet Pressure Gauges
- Removable Dome for easy clean out
- Automatic purge valve with timer
- ASME certified for 150 PSIG @ 210°F
- 304, 316 Stainless Steel construction

* PRESSURE DROP *

To determine pressure drop (PSI) at known flow rates, use the following formula:

$$P = \left(\frac{\text{GPM}}{75} \right)^2$$



Note - All dimensions are approximate and are subject to change without notice.

Weight (empty): 142 lbs
 Weight (full): 229 lbs
 Volume: 10.5 gallons

SBS		SBS CORPORATION	
81 MILL STREET • ROCHESTER, MI 48307 • USA			
U.S. & Canada 1-800-662-8776 • Fax 1-248-652-4303 • www.sbscorporation.com			
CUSTOMER:			
DRAWN BY: GSB	DATE: 6/5/02	SCALE: 1 : 16	
CS-300 Centrifugal Separator			